



# PoolMoss<sup>®</sup> for Ponds

## Use Instructions

### Installation

	0-10,000 gallons	10-20,000 gallons	Above 20,000 gallons
Contact Chambers	2 CC-F	1 CC-STxS	Contact us

1. Open black contact chamber.
2. Insert PoolMoss<sup>®</sup> for ponds starter packet into contact chamber. (*Option – insert a few rocks into dispenser to weigh down to bottom*)
3. Snap contact chamber closed.
4. Insert contact chamber into pond in an area with significant water flow – ideally underneath a waterfall feature.

### Maintenance

- Change moss every 30 days. After first month, use PoolMoss<sup>®</sup> maintenance dose.
- When changing PoolMoss<sup>®</sup> for ponds: remove old PoolMoss<sup>®</sup> from contact chamber and dispose.
- Replace with new moss refill. Insert contact chamber back into pond.
- If winterizing your pond, simply remove the contact chamber, dispose or compost refill contents, and clean and store contact chamber.
- If treating the pond with algaecide or shock or chlorine levels above 5 ppm, remove contact chamber from water before treatment and reinstall after algaecide dissipates or sanitizer levels return to desired range.
- Do not change water in the pond unless water quality requires it. PoolMoss<sup>®</sup> conditions water over time, and if the water is changed, you are removing much of what has been put into the water.
- When water is changed, change the PoolMoss<sup>®</sup> as well for best results.



## Storage and Handling

- Keep PoolMoss<sup>®</sup> Starter and PoolMoss<sup>®</sup> Maintenance dry until use.
- PoolMoss<sup>®</sup> is good for ponds up to 10,000 gallons



## Support:

For technical support please contact us or your authorized dealer.

### Contact Information

#### Creative Water Solutions

13809 Industrial Park Blvd.

Plymouth, MN 55441

**Phone** (763) 398-0141

**Fax** (763) 551-2572

[info@cwsnaturally.com](mailto:info@cwsnaturally.com)

[www.cwsnaturally.com](http://www.cwsnaturally.com)

